

Boat Manufactured By:



PO Box 65 • New Paris, IN
(866) 719-7873
www.sylvanmarine.com



SYLVAN® S5 EXTREME TWIN

Length	26' 10"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	4,000 lbs
Maximum HP	600 hp
Fuel Capacity	120 gal
Pontoon # / Diameter	3 / 25"
Weight as Tested	6,314 lbs

F300XCA / LF300XCA

Horsepower	300 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	562 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#4
------------------------	----

PROPELLER(S)

Series	Saltwater Series II™
Diameter x Pitch	15 1/4 x 18
Yamaha Part #	6CE-45934-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	66° F / 72° F
Elevation (in feet above sea level)	860'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 100 gallons of fuel, 2 batteries, safety and test gear.

YPB#: PB_SYL_S5ExtremeTwin_t_F300XCA_2017-07-30_PNT

Engine: Yamaha F300XCA / LF300XCA

Boat: Sylvan® S5 Extreme Twin

Configuration: Twin

Test Date: 30-Jul-2017

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	6	2.6	2.31
1500	8.8	4.4	2
2000	14.6	6.2	2.36
2500	20.8	9.6	2.17
3000	25.7	12.2	2.11
3500	31.1	16.3	1.91
4000	36.1	21.8	1.66
4500	41.4	27	1.53
5000	45	34.4	1.31
5500	50.7	41.1	1.23
6000	55.8	51.2	1.09
0-20 MPH: 3.48			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.